



OH Line Tensioning

Webbing Strap Type Ratchet Lever Hoists



Series 250A
(Model 250DA shown)



Series 322B-344DHB
(Models DA with hot stick hook shown)




Series 6000
(Model 6000DA shown)

Description:

Ratchet lever hoist with webbing strap, cast aluminium and zinc alloy main body parts and fibreglass handle. Design safety factor 4:1, individually tested at 125% rated load.


Choice of Hooks:



Standard Hook
Heat-treated, forged steel hooks provide lasting strength and durability. Hooks will bend open under extreme overload situations, but will not break. Safety latches are



Hot Stick Hook
Hot Stick Hooks have a welded ring for use with holding sticks. Safety latches are standard.



Swivel Gate Hook
Bullard-type, swivel gate latch provides positive locking action for secure load holding in all environments.



Hot Stick Hook & Gate Latch
Hot Stick Gate latch models have rings on the latch and the hook for use on energized lines. Holding sticks easily manoeuvre the latch and hooks.

WARNING: The equipment shown is intended for industrial use only and should not be used to lift, support, or otherwise transport people, or to suspend loads over people.



OH Line Tensioning

Webbing Strap Type Ratchet Lever Hoists

CODE	Features	SINGLE LINE			DOUBLE LINE			HOIST DATA			
		Capacity	Lift	Minimum Distance between Hooks	Capacity	Lift	Minimum Distance between Hooks	Web Strap Length	Handle length	Hook throat opening	Net weight
		kg (lbs)	m (ft)	mm (in)	kg (lbs)	m (ft)	mm (in)	m (ft)	mm (in)	mm (in)	kg (lbs)
250A		453 (1000)	2.7 (9)	533 (21)	907 (2000)	1.3 (4.25)	635 (25)	3.0 (10)	508 (20)	22.22 r(7/8)	5.2 (11.5)
250DA		453 (1000)	2.87 (9.25)	457 (18)	907 (2000)	1.3 (4.25)	635 (25)	3.0 (10)	508 (20)	22.22 r(7/8)	5.4 (12)
250CA		453 (1000)	2.7 (9)	533 (21)	907 (2000)	1.3 (4.25)	635 (25)	3.0 (10)	508 (20)	22.22 r(7/8)	5.2 (11.5)
250DHA		453 (1000)	2.8 (9.25)	457 (18)	907 (2000)	1.3 (4.25)	635 (25)	3.0 (10)	508 (20)	22.22 r(7/8)	5.4 (12)
322B		680 (1500)	4.26 (14)	508 (20)	1360 (3000)	2.1 (7)	584 (23)	4.57 (15)	609 (24)	22.2 r(7/8)	5.2 (11.5)
322DB		680 (1500)	4.26 (14)	508 (20)	1360 (3000)	2.1 (7)	584 (23)	4.57 (15)	609 (24)	22.2 r(7/8)	5.2 (11.5)
322CB		680 (1500)	4.26 (14)	584 (23)	1360 (3000)	2.1 (7)	698 (27.5)	4.57 (15)	609 (24)	22.2 r(7/8)	5.2 (11.5)
322DHB		680 (1500)	4.26 (14)	558 (22)	1360 (3000)	2.1 (7)	660 (26)	4.57 (15)	609 (24)	22.2 r(7/8)	5.4 (12)
344B		907 (2000)	3.35 (11)	508 (20)	1818 (4000)	1.67 (5.5)	584 (23)	3.65 (12)	762 (30)	25.4 *(1)	5.2 (11.5)
344DB		907 (2000)	3.35 (11)	508 (20)	1818 (4000)	1.67 (5.5)	584 (23)	3.65 (12)	762 (30)	25.4 *(1)	5.4 (12)
344CB		907 (2000)	3.35 (11)	584 (23)	1818 (4000)	1.67 (5.5)	698 (27.5)	3.65 (12)	762 (30)	25.4 *(1)	5.2 (11.5)
344DHB		907 (2000)	3.35 (11)	558 (22)	1818 (4000)	1.67 (5.5)	660 (26)	3.65 (12)	762 (30)	25.4 *(1)	5.4 (12)
6000A					2721 (6000)	1.5 (5)	685 (27)	3.65 (12)	762 (30)	28.5 r(1 1/16)	12.04 (26.5)
6000DA					2721 (6000)	1.5 (5)	685 (27)	3.65 (12)	762 (30)	28.5 r(1 1/16)	12.04 (26.5)
6000CA					2721 (6000)	1.5 (5)	800 (31.5)	3.65 (12)	762 (30)	28.5 r(1 1/16)	12.04 (26.5)

All models meet ASME/ANSI Safety Standard B30-21

Includes Hot Stick Rings on All Hooks, Control Surfaces and Quick Disconnect Shaft.

Includes Swivel-Type Gate on All Hooks.

Includes Hot Stick-Type Gate Latch on All Hooks as well as Hot Stick rings on All Hooks, Control Surfaces and Quick Disconnect Shaft.

When dry and clean, webbing has dielectric properties typical of nylon and polyester.

r Dimensions for all hooks.

□ Dimensions for these hooks. Refer to product illustration on page 12.

Dimensions for this hooks; throat opening 22.2mm (7/8"). Refer to product illustration on page 12.